



US010356332B2

(12) **United States Patent**  
**Cohen et al.**

(10) **Patent No.:** **US 10,356,332 B2**  
(45) **Date of Patent:** **Jul. 16, 2019**

(54) **DUAL APERTURE ZOOM CAMERA WITH VIDEO SUPPORT AND SWITCHING / NON-SWITCHING DYNAMIC CONTROL**

(71) Applicant: **Corephotonics Ltd.**, Tel-Aviv (IL)

(72) Inventors: **Noy Cohen**, Tel-Aviv (IL); **Oded Gigushinski**, Herzlia (IL); **Nadav Geva**, Tel-Aviv (IL); **Gal Shabtay**, Tel-Aviv (IL); **Ester Ashkenazi**, Modi'in (IL); **Ruthy Katz**, Tel Aviv (IL); **Ephraim Goldenberg**, Ashdod (IL)

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/241,505**

(22) Filed: **Jan. 7, 2019**

(65) **Prior Publication Data**

US 2019/0158753 A1 May 23, 2019

**Related U.S. Application Data**

(63) Continuation of application No. 15/324,720, filed as application No. PCT/IB2016/053803 on Jun. 26, 2016.

(Continued)

(51) **Int. Cl.**  
**H04N 5/225** (2006.01)  
**H04N 5/232** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **H04N 5/23296** (2013.01); **H04N 5/2258** (2013.01); **H04N 5/23216** (2013.01); **H04N 5/23245** (2013.01)

(58) **Field of Classification Search**  
CPC ..... H04N 5/23296; H04N 5/2258; H04N 5/23216; H04N 5/23245  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,199,785 A 4/1980 McCullough et al.  
5,005,083 A 4/1991 Grage et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101276415 A 10/2008  
CN 102739949 A 10/2012  
(Continued)

OTHER PUBLICATIONS

Statistical Modeling and Performance Characterization of a Real-Time Dual Camera Surveillance System, Greienhagen et al., Publisher: IEEE, 2000, 8 pages.

(Continued)

*Primary Examiner* — Nhan T Tran

(74) *Attorney, Agent, or Firm* — Natha & Associates; Menachem Nathan

(57) **ABSTRACT**

A dual-aperture zoom digital camera operable in both still and video modes. The camera includes Wide and Tele imaging sections with respective lens/sensor combinations and image signal processors and a camera controller operatively coupled to the Wide and Tele imaging sections. The Wide and Tele imaging sections provide respective image data. The controller is configured to output, in a zoom-in operation between a lower zoom factor (ZF) value and a higher ZF value, a zoom video output image that includes only Wide image data or only Tele image data, depending on whether a no-switching criterion is fulfilled or not.

**22 Claims, 5 Drawing Sheets**

