



US010620450B2

(12) **United States Patent**
Shabtay et al.

(10) **Patent No.:** **US 10,620,450 B2**
(45) **Date of Patent:** ***Apr. 14, 2020**

(54) **THIN DUAL-APERTURE ZOOM DIGITAL CAMERA**

(71) Applicant: **Corephotonics Ltd.**, Tel-Aviv (IL)

(72) Inventors: **Gal Shabtay**, Tel-Aviv (IL); **Ephraim Goldenberg**, Ashdod (IL)

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/299,450**

(22) Filed: **Mar. 12, 2019**

(65) **Prior Publication Data**

US 2019/0212574 A1 Jul. 11, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/456,506, filed on Mar. 11, 2017, now Pat. No. 10,288,896, which is a (Continued)

(51) **Int. Cl.**
G02B 27/64 (2006.01)
G02B 9/60 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G02B 27/646** (2013.01); **G02B 1/041** (2013.01); **G02B 9/60** (2013.01); **G02B 13/009** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC .. H04N 5/2254; H04N 5/2258; H04N 5/2257; H04N 5/23296; H04N 9/045;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,106,752 A 2/1938 Land
2,354,503 A 7/1944 Cox
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101276415 A 10/2008
CN 102739949 A 10/2012
(Continued)

OTHER PUBLICATIONS

Statistical Modeling and Performance Characterization of a Real-Time Dual Camera Surveillance System, Greienhagen et al., Publisher: IEEE, 2000, 8 pages.

(Continued)

Primary Examiner — Luong T Nguyen
(74) *Attorney, Agent, or Firm* — Nathan & Associates; Menachem Nathan

(57) **ABSTRACT**

A dual-aperture zoom camera comprising a Wide camera with a respective Wide lens and a Tele camera with a respective Tele lens, the Wide and Tele cameras mounted directly on a single printed circuit board, wherein the Wide and Tele lenses have respective effective focal lengths EFL_W and EFL_T and respective total track lengths TTL_W and TTL_T and wherein $TTL_W/EFL_W > 1.1$ and $TTL_T/EFL_T < 1.0$. Optionally, the dual-aperture zoom camera may further comprise an optical OIS controller configured to provide a compensation lens movement according to a user-defined zoom factor (ZF) and a camera tilt (CT) through $LMV = CT * EFL_{ZF}$, where EFL_{ZF} is a zoom-factor dependent effective focal length.

18 Claims, 9 Drawing Sheets

