



US009661233B2

(12) **United States Patent**
Shabtay et al.

(10) **Patent No.:** **US 9,661,233 B2**
(45) **Date of Patent:** ***May 23, 2017**

(54) **DUAL APERTURE ZOOM DIGITAL CAMERA**

(56) **References Cited**

(71) Applicant: **Corephotonics Ltd.**, Tel-Aviv (IL)

7,305,180 B2 12/2007 Labaziewicz et al.
7,561,191 B2 7/2009 May et al.

(72) Inventors: **Gal Shabtay**, Tel-Aviv (IL); **Ephraim Goldenberg**, Ashdod (IL); **Oded Gigushinski**, Tel-Aviv (IL); **Noy Cohen**, Tel-Aviv (IL)

(Continued)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

JP 08-114771 A 5/1996
JP 10-173966 A 6/1998

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 5 days.

OTHER PUBLICATIONS

This patent is subject to a terminal disclaimer.

Barbara Zitova and Jan Flusser; Image Registration Methods: a Survey, Image and Vision Computing; 21 (2003): 977-1000; pp. 978, 987-993.*

(Continued)

(21) Appl. No.: **14/880,251**

Primary Examiner — Roberto Velez

(22) Filed: **Oct. 11, 2015**

Assistant Examiner — Cynthia Segura

(65) **Prior Publication Data**

US 2016/0050374 A1 Feb. 18, 2016

(74) *Attorney, Agent, or Firm* — Nathan & Associates Patent Agents Ltd.; Menachem Nathan

Related U.S. Application Data

(63) Continuation of application No. 14/365,711, filed on Jun. 16, 2014, now Pat. No. 9,185,291.

(57) **ABSTRACT**

(51) **Int. Cl.**
H04N 5/232 (2006.01)
H04N 5/225 (2006.01)
G02B 13/00 (2006.01)

A dual-aperture zoom digital camera operable in both still and video modes. The camera includes Wide and Tele imaging sections with respective lens/sensor combinations and image signal processors and a camera controller operatively coupled to the Wide and Tele imaging sections. The Wide and Tele imaging sections provide respective image data. The controller is configured to combine in still mode at least some of the Wide and Tele image data to provide a fused output image from a particular point of view, and to provide without fusion continuous zoom video mode output images, each output image having a given output resolution, wherein the video mode output images are provided with a smooth transition when switching between a lower zoom factor (ZF) value and a higher ZF value or vice versa, and wherein at the lower ZF the output resolution is determined by the Wide sensor while at the higher ZF value the output resolution is determined by the Tele sensor.

(52) **U.S. Cl.**
CPC **H04N 5/23296** (2013.01); **G02B 13/009** (2013.01); **H04N 5/225** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04N 5/23245; H04N 5/23296
(Continued)

18 Claims, 8 Drawing Sheets

